



### Main

Range of product	Conext
Device short name	ComBox
Product or component type	Communication device

### Complementary

[Us] rated supply voltage	9...24 V DC
Power consumption in W	10 W (peak) ≤ 2 W (typical)
Memory description	External - micro SD card (up to 2 GB) Internal - Flash disk (96 MB)
Communication port protocol	1 USB, connector type: USB type B 1 USB, connector type: USB type A 1 Modbus, connector type: screw connector, communication interface: RS485, transmission rate: 19200 bit/s 1 Ethernet, connector type: RJ45, transmission rate: 10/100 Mbit/s 2 Xanbus, connector type: RJ45
System requirements	Internet browser Android
Function available	Update firmware monitoring Embedded data logger
Output type	Relay
Local signalling	LED (5) for status
Type of installation	Indoor
Fixing mode	By 2 screws
Mounting support	35 mm DIN rail
Material	ABS (acrylonitrile butadiene-styrene)
Electromagnetic compatibility	Conducted and radiated emissions, class B conforming to FCC Part 15 Conducted and radiated emissions, class B conforming to ICES-003 Emission standard for residential, commercial and light-industrial environments conforming to EN 61000-6-3 Immunity for residential, commercial and light-industrial environments conforming to EN 61000-6-1
Height	114 mm
Width	169 mm
Depth	54 mm
Product weight	0.25 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

IP degree of protection	IP20
NEMA degree of protection	NEMA 1
Ambient air temperature for operation	-40...85 °C
Ambient air temperature for storage	-40...85 °C
Product certifications	CE RCM
Relative humidity	<= 95 %