

Intelligent Solar System Controller

suitable for use in small solar home systems with 15 Amp and load power capacity up 240 Wp. Load such as light, mobile chargers, small TVs and radios can be switched off manually on the controller without additional wall mounted switches. In professional applications such as telecommunications and traffic management technology, the controller can also be used in small photovoltaic power supply system. The electronic fuse makes the controller completely maintenance-free and robust. Thanks to the universal series switching technology the controller can be used with amorphous, thin film and crystalline solar modules.



PRODUCT NAME	MODEL NUMBER
ELECTRISOL-SA	ELE-PV-1510

Application: Lighting, Solar Residential System, Recreational Vehicles, Marine Boat

www.electrilabs.co.za

- Product Features**
- Microcontroller digital accuracy
 - Voltage series regulation
 - PWM control
 - State of Charge (SoC) advanced technology
 - Temperature compensation
 - Common positive grounding

- Electronic Protection Functions**
- Overcharge protection
 - Deep discharge protection
 - Reverse polarity protection of load, module and battery
 - Automatic electronic fuse
 - Short circuit protection of load and module
 - Overvoltage protection at module input
 - Open circuit protection without battery
 - Reverse current protection at night
 - Overload protection
 - Battery overvoltage shutdown

- Displays**
- 3 LEDs show operating states - for operation, SoC, fault message

- Operation**
- Manual load switch with automatic re-start

- Certificates**
- CE compliant according EN61000-6-1 and EN61000-3
 - UL 1741 compliant
 - RoHS compliant
 - Manufactured according to ISO 9001 and ISO 14001



MODEL NUMBER	1510
Operating Performance	
System Voltage	12 V
Typical Idle Consumption	< 10 mA
DC input side	
Open circuit voltage solar module	<29 V
Max. input current	15 A
DC output side	
Max. load current	15 A
End of charge voltage	13.4 V ... 14.2V
Boost charge voltage	14.4 V
Reconnection voltage (LVR)	12.5 V
Deep discharge protection (LVD)	11 V ... 11.6 V
Operating Conditions	
Ambient Temperature	-20°C +50°C
Fitting and construction	
Terminal (fine/single wire)	16 mm ² / 25 mm ² - AWG 6 / 4
Protection Degree	IP 32
Dimension (X x Y x Z)	169 x 97 x 44 mm
Weight	160 g
Technical data at 25°C/77°F	

