

**Intelligent Solar System Controller** best seller of one of the most used SHS controller. With high power up to 15A they fit to a system up to 240 Wp. The circuit board is completely electronically protected and a large display informs the users about all operating modes with the aid of symbols including voltage, current and state of charge. Large terminals guarantee a simple connection of solar panel, battery and load.



**PRODUCT NAME**  
ELECTRISOL-SA

**MODEL NUMBER**  
ELE-PV-1520

**Application:** Solar Residential System, Recreational Vehicles, Marine Boat

[www.electrilabs.co.za](http://www.electrilabs.co.za)

**Product Features**


- Microcontroller digital accuracy
- Voltage series regulation
- PWM control
- State of Charge (SoC) advanced technology
- Temperature compensation
- Common positive grounding

**Electronic Protection Functions**

- Overcharge protection
- Deep discharge protection
- Reverse polarity protection of load, module and battery
- Automatic electronic fuse
- Short circuit protection of load and module
- Overvoltage protection at module input
- Open circuit protection without battery
- Reverse current protection at night
- Overload protection
- Battery overvoltage shutdown

**Displays**

- Graphical LCD Display shows operating states - for operation state of charge, fault messages



**Operation**

- Manual load switch

**Certificates**

- CE compliant according EN61000-6-1 and EN61000-3
- UL 1741 compliant
- RoHS compliant
- Manufactured according to ISO 9001 and ISO 14001

**MODEL NUMBER**

1520

**Operating Performance**

System Voltage 12 V  
Typical Idle Consumption < 20 mA

**DC input side**

Open circuit voltage solar module < 29 V  
Max. input current 15 A

**DC output side**

Max. load current 15 A  
End of charge voltage 13.4 V ... 14.2V  
Boost charge voltage 14.4 V  
Reconnection voltage (LVR) 12.5 V  
Deep discharge protection (LVD) 11 V ... 11.5 V

**Operating Conditions**

Ambient Temperature -20°C ..... +50°C

**Fitting and construction**

Terminal (fine/single wire) 16 mm<sup>2</sup> / 25 mm<sup>2</sup> - AWG 6 / 4  
Degree of protection IP 32  
Dimension (X x Y x Z) 169 x 97 x 44 mm  
Weight 350 g

*Technical data at 25°C/77°F*

